

Section V – HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE See Sec. II
EFFECT OF OVEREXPOSURE - Moderate eye irritant. Possible irritation of skin by solvent. Irritation or narcosis can result from inhalation of solvent vapors.

RECOMMENDED FIRST AID PROCEDURES
SKIN CONTACT - wipe off with a rag then thoroughly rinse with water and wash with mild soap and water.
EYE CONTACT - flush 10 minutes with water and consult eye physician.
INHALATION - remove to fresh air.

Section VI – REACTIVITY DATA

UNSTABLE STABLE
STABILITY (Materials to avoid)
DECOMPOSITION PRODUCTS

CONDITIONS TO AVOID Avoid sparks from being struck with steel object or static electricity. Avoid open flame in vicinity. Avoid exposure to heat.

POLYMERIZATION MAY OCCUR WILL NOT OCCUR
IS TO AVOID

Section VII – SPILL OR LEAK PROCEDURES

ACTIONS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Absorb with oil absorbent compound or dry rags. Wash with large volume of water. Dispose of rags by wetting with water and keep in closed container.

DISPOSAL METHOD Dispose in tightly closed metal container and finally dispose by sanitary landfill.

Section VIII – SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION

Good ventilation

ADDITIONAL INFORMATION Use adequate ventilation using exhaust fan.

PROTECTIVE GLOVES - yes
RESPIRATORY PROTECTION - yes
ADDITIONAL PROTECTIVE EQUIPMENT

Section IX – SPECIAL PRECAUTIONS

ACTIONS TO BE TAKEN IN HANDLING AND STORING Use normal storing precautions as with any paint. Keep away from heat, sparks or open flame.

ADDITIONAL PRECAUTIONS

Avoid prolonged inhalation of vapors